

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E01C 13/04, 5/20, E04F 15/10, A63C 19/12	A1	(11) International Publication Number: WO 98/46830 (43) International Publication Date: 22 October 1998 (22.10.98)
(21) International Application Number: PCT/FI98/00307 (22) International Filing Date: 8 April 1998 (08.04.98) (30) Priority Data: 971594 16 April 1997 (16.04.97) FI (71) Applicant (for all designated States except US): VARIFORM OY [FI/FI]; Matalasalmenkuja 1, FIN-00150 Helsinki (FI). (72) Inventor; and (75) Inventor/Applicant (for US only): VALTANEN, Jarkko [FI/FI]; Aurorankatu 15 B 19, FIN-00101 Helsinki (FI). (74) Agent: KANGASMÄKI, Reijo; Finnish Patent Consulting FPC, Hermiankatu 14, FIN-33720 Tampere (FI).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Finnish).</i>
(54) Title: JOINT ARRANGEMENT (57) Abstract <p>The invention relates to a joint arrangement for a surface structure, such as a protecting plate, element or the like, which surface structure is meant particularly for covering of ground together with one or several other surface structures for temporary protecting, coating and/or like of the ground. In connection with the surface structure there has been arranged at least a joint arrangement for removable attachment of one or several adjacent surface structures to the same and the thermal insulation (1), that comprises at least one, essentially plastic based, such as cellular, expanded, foamed plastic structured or a like thermal insulation layer (1'). The joint arrangement comprises a joint piece (x), by means of which the surface structures may be coupled with each other essentially by corners of the same by means of a locking assembly (y) operating advantageously by quick-locking principle.</p> <div style="text-align: right;"> </div>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Joint arrangement

The invention relates to a joint arrangement for a surface structure, such as a protecting plate, element or a like, which surface structure is meant particularly for covering of ground together with one or several other surface structures for temporary protecting, coating and/or like of the ground. In connection with each surface structure there has been arranged at least a joint arrangement for removable attachment of one or several adjacent surface structures to the same and a thermal insulation, that comprises at least one, essentially plastic based, such as cellular, expanded, foamed plastic structured or a like thermal insulation layer. The joint arrangement comprises a joint piece, that is to be coupled by means of a locking assembly, for coupling of the adjacent surface structures with each other essentially by corners of the same, which joint piece comprises known as such a right-angled, such as a square shaped frame part, whereby the locking assembly is arranged by projections placed at the corners of the frame part and preferably by recesses of the same shape, that are placed underside the surface structure. To the bottom surface of the surface structure there has been arranged preferably an integral support arrangement, that comprises a platform structure projecting from the basic wall thickness of the surface structure, such as the thermal insulation layer.

30

For the purpose above, particularly for covering a field of grass or e.g. of ice, it is previously known to use most heterogeneous arrangements. For example covering elements being sold nowadays by the name TERRAPLAS represent particularly more developed solutions, that are made of plastics by injection moulding. To minimize mass of the covering element in question, it has been produced as a perforated

35

structure in a way, that not any actual thermal insulation effect may be achieved by the type of covering element. Correspondingly the support arrangements to support the covering elements against the ground must furthermore be attached to the covering elements by means of totally separate auxiliary devices and work stages. In addition to this locking arrangements connecting the covering elements to each other must be attached separately as well, so that a uniform and seamless covering may be achieved by the type of covering elements. The "perforated" structure of the type of covering element above does not either enable exploitation of a so called green house phenomenon particularly in connection with a grass field.

The perforated structure of the covering element in question is naturally advantageous with a view to the breathing of the ground, but the perforation causes in addition to a "rough" appearance and to those thermal insulation problems being described above such disadvantage as well, that garbage may get collected between the covering and the ground, which naturally eliminates good points of the covering element in question in this respect.

On the other hand it is previously known to use e.g. styrox particularly for covering of ice fields, that has been surrounded by both sides of the same by plywood plate. This type of solution is naturally not applicable as such to be installed particularly on a grass field, in case not totally separate foot structures are being used to raise the covering structure apart from the ground. On the other hand when being used in connection with an ice field, such problem of this type of solution has been found, that the plywood plates tend to freeze to the ice, that is why loosening of the same is laborious. In addition to that the type of constructions are very heavy, that is why

storing as well as use of the same for actual coating is disproportionately difficult.

5 On the other hand Finnish Patent Application No. 964199 discloses a protective structure, the thermal insulation of which comprises advantageously a plastic based, such as cellular, expanded, foamed plastic structured and/or a like thermal insulation layer, to the bottom surface of which there has been arranged an
10 integral support arrangement, that comprises a platform structure projecting from the basic wall thickness of the thermal insulation layer particularly in order to achieve an air space between the protective structure and the ground under the same.

15 The solution in question is very advantageous in practice, which is due to the fact, that the thermal insulation placed between the ground and the protective structure gets more efficient thanks to the air
20 space between the protective structure and the ground. In this case the feet, that are arranged as an integral platform structure directly to the bottom surface of the thermal insulation layer, prevent first of all so called burning of the grass that is left under the
25 protective structure. In the application in question there has been shown furthermore an advantageous embodiment for coupling of the protective structures with each other by means of joint arrangements, that are arranged to the protective structures in an
30 integral manner during manufacturing of the same and that operate e.g. by quick-locking principle. During tests in practice it has been found justified to improve particularly the joint arrangement coupling the protective structures with each other in such
35 respect, that the protective structures could be on the other hand assembled as easily as possible but however locked in connection with each other reliably and seamlessly.

E.g. application document DE 27 17 625 discloses a covering assembly, that is applicable for temporary covering of ground in principle, wherein three or four covering elements being placed on the ground are being attached by means of a joint piece coupling the covering elements together by the corners of the same and that has holding rings of suitable shape for arrowlike locking pins, that are placed at the corners of the covering elements. The joint pieces being used in this solutions are placed, however, essentially underneath the actual covering elements, that is why they must be sunk into the ground, that is why they are not applicable as such to be used in connection with the type of thin surface structures as being discussed in this connection. On the other hand application document DE 25 58 967 discloses a base structure arrangement, that is to be put together e.g. by stone based elements, in which e.g. four bottom plates are being attached by corners of the same by means of a square shaped joint piece. At corners of the same there are pins, that may be attached to corresponding holes being placed at the corners of the bottom plate. This solution is not either applicable to be used for the type of use of the invention in question, because the bottom plates get supported by the corners of the same on the joint pieces. That is why with the type of solution as such, an entirety operating satisfactorily enough may not be achieved in connection with thin plastic structured covering elements being included to the invention in question. Furthermore application document DE 44 14 341 discloses separate joint arrangements to be used for connecting of concrete plates, that are intended for the corresponding purpose as the above application document. This solution is not as described above either applicable to be used for the type of use of the invention in question, whereby an adequately functioning entirety may not be achieved either, particu-

larly when being used in connection with thin plastic structured covering elements.

5 It is the aim of the joint arrangement according to this invention to achieve a decisive improvement for this purpose in other words particularly for making the installation of a removable covering structure more efficient and for securing staying together of the same and thus to raise substantially the level of
10 prior art. To achieve this aim the joint arrangement according to the invention is primarily characterized in, that the frame part of the joint piece, that has an open center, such as a framework-like structure is arranged to pass the recesses existing in the platform
15 structure, whereby the height of the recesses is arranged to correspond essentially at least to the thickness of the frame part.

20 As the most important advantages of the joint arrangement according to the invention may be mentioned easy installation of the surface structures enabled by a joint piece belonging to the same as well as simplicity and technical workability of the construction and manufacturing of the same as well. The invention
25 enables first of all a very smooth covering, which is applicable for most heterogeneous purposes, that is carried out by joint pieces, that remain out of sight under the corners of the surface structures during the installation phase, whereby the surface structures to
30 be coupled with each other may be connected to each other very quickly to form a surface structure, that is adequately smooth and seamless. As an advantageous embodiment the joint piece has a square shaped framework, by means of which e.g. four surface structures
35 may be connected with each other by means of one joint piece operating by quick-locking principle, e.g. by cooperation of locking recesses, that are placed at the corners of the same, and projections, that are

placed at the corners of the joint piece. As an advantageous embodiment the frame part of the joint piece is arranged furthermore to pass the recesses of the platform structure in a way, that the total thickness of the surface structure is not increased therefor. Furthermore, when male couplers, that are placed advantageously at opposite edges of each surface structure, and female couplers, that are placed correspondingly at opposite edges, are being used and that are being placed furthermore at the bottom edges of the outer edges of the surface structures, the covering structure may be coupled in an extremely simple way by continuously "dropping" the following surface structure to be installed from above to its place and by connecting the same to the already installed surface structures by means of joint pieces by corners of the same.

Advantageous embodiment of the joint arrangement according to the invention are represented in the dependent claims related to the same.

In the following description, the invention is illustrated in greater detail with reference to the appended drawings, in which

Fig. 1 shows one advantageous surface structure related to the joint arrangement according to the invention,

30

Figs 2a - 2c

show furthermore the surface structure being shown in fig. 1 as a detail seen from above (2a), and some advantageous coupling means arrangements as partial side-views for the part of female couplers (2b) and male couplers (2c), and

35

Figs 3a and 3b

show an advantageous joint piece belonging to the joint arrangement according to the invention as a side-view and seen from above.

5

The invention relates to a joint arrangement for a surface structure, such as a protecting plate, element or a like, which surface structure is meant particularly for covering of ground together with one or several other surface structures for temporary protecting, coating and/or like of the ground. In connection with each surface structure there has been arranged at least a joint arrangement for removable attachment of one or several adjacent surface structures to the same and thermal insulation 1, that comprises at least one, essentially plastic based, such as cellular, expanded, foamed plastic structured or a like thermal insulation layer 1'. The joint arrangement comprises a joint piece x, that is to be coupled by means of a locking assembly y, for coupling of the adjacent surface structures with each other essentially by corners of the same, which joint piece x comprises known as such a right-angled, such as a square shaped frame part, whereby the locking assembly y is arranged by projections y1 placed at the corners of the frame part and preferably by recesses y2 of the same shape, that are placed underside the surface structure. To the bottom surface of the surface structure there has been arranged preferably an integral support arrangement 1a, that comprises a platform structure projecting from the basic wall thickness s of the surface structure, such as the thermal insulation layer 1'. The frame part x1 of the joint piece x, that has an open center, such as a framework-like structure is arranged to pass the recesses 1a' existing in the platform structure 1a, whereby the height of the recesses is arranged to correspond essentially at least to the thickness h of the frame part x1.

10

15

20

25

30

35

With reference particularly to figs 1 and 2, at each corner of the surface structure there has been arranged two recesses y2 one after the other at each side. This enables first of all that, that with only one joint piece x e.g. as shown in figs 3a and 3b it is possible to couple four surface structures with each other by the corners of the same or e.g. when a straight gable edge is being formed only two surface structures side by side.

10

Furthermore with reference to fig. 2a, the platform structure 1a is arranged by single and square shaped platforms 1a", that are placed advantageously all over the bottom surface of the surface structure, whereby the frame part x1 of the joint piece is arranged to embed preferably for platforms 1a".

15

As an advantageous embodiment, the surface structures are square shaped, the dimensions of which are e.g. 1500 x 1500 mm, in which case the joint arrangement comprises coupling means z, such as male-female couplers z1, z2 being placed at the outer edges of the surface structure, that are carried out in the solution according to the invention advantageously in a way, that both the male and female couplers z1, z2 are arranged at opposite outer edges of the surface structure as shown in fig. 1. Furthermore as an advantageous embodiment with reference particularly to figs 2b and 2c, the male couplers z1 are arranged by projections being placed at the lower edges of the longitudinal p1 outer edges of the surface structure and correspondingly the female couplers z2 by recesses being placed at the lower edges of the crosswise p2 outer edges. In this way particularly coupling of the surface structures with each other is enabled in a way, that the following surface structure to be installed may be attached to the surface structures, that are installed already on the ground, after coup-

25

30

35

ling of the male coupler z1 existing at the outer edge of the same by lowering thereafter the outer surface being equipped with female coupler z2 essentially freely from above to its place and by locking the corners of the same to the above by means of joint pieces x.

Furthermore as an advantageous embodiment with reference to the views shown particularly in figs 2b and 2c, the male and female couplers z1, z2 comprise furthermore an auxiliary support/sealing assembly z3, that is carried out by such as counterpart surfaces or the like being placed at the upper edge of the outer surface of the surface structure at an angle α , that deviates essentially from the vertical direction, preferably at an angle of 15° and being directed to opposite direction and/or to the same direction in respect to the surface structure. With counterpart surfaces being directed to opposite directions it is first of all possible to achieve an auxiliary locking arrangement of a so called snap-joint type, and by means of counterpart surfaces being directed to the same direction as shown in figs 2b and 2c, the joint between the surface structures may get sealed.

It is obvious, that the invention is not limited to the embodiments presented or described above, but it can be modified within the basic idea even to a great extent. In this connection it is naturally possible to equip the surface structure to be used in connection with the joint arrangement more abundantly by exploiting e.g. separate support arrangements according to traditional practice or auxiliary reinforcing plates or the like in the surface structures. It is furthermore naturally possible to put up each single surface structure e.g. of several frame parts, that are connected to each other by suitable fastening arrangements either during manufacturing or that may be put

together during installation in site. In this connection the surface structures may be connected by other types of joint pieces also, deviating from the type of joint piece being shown above, which reach e.g. further to the center parts of the surface structure. It is furthermore naturally possible to use different kinds of coatings, also, for coating of the surface structure either by the upper surface or the bottom surface of the same. Correspondingly the surface structure as such or the thermal insulation layer belonging to the same may be made of EPS-material, such as expanded polystyrene foam or styrox, XPS-material, such as extruded polystyrene foam, EPP-material, such as expanded polypropylene foam or extruded polyethylene foam or e.g. extruded PVC-structural foam sheet. In a corresponding manner it is naturally possible to make the joint piece belonging to the joint arrangement of most heterogeneous materials, such as of wood, metal, plastics, reinforced plastics, ceramics etc.

Claims

1. Joint arrangement for a surface structure, such as a protecting plate, element or the like, which surface structure is meant particularly for covering of ground together with one or several other surface structures for temporary protecting, coating and/or like of the ground, whereby in connection with each surface structure there has been arranged at least a joint arrangement for removable attachment of one or several adjacent surface structures to the same and thermal insulation (1), that comprises at least one, essentially plastic based, such as cellular, expanded, foamed plastic structured or a like thermal insulation layer (1'), whereby the joint arrangement comprises a joint piece (x), that is to be coupled by means of a locking assembly (y), for coupling of the adjacent surface structures with each other essentially by corners of the same, which joint piece (x) comprises known as such a right-angled, such as a square shaped frame part, whereby the locking assembly (y) is arranged by projections (y1) placed at the corners of the frame part and preferably by recesses (y2) of the same shape, that are placed underside the surface structure, and whereby to the bottom surface of the surface structure there has been arranged preferably an integral support arrangement (1a), that comprises a platform structure projecting from the basic wall thickness (s) of the surface structure, such as the thermal insulation layer (1'), **characterized** in, that the frame part (x1) of the joint piece (x), that has an open center, such as a framework-like structure is arranged to pass the recesses (1a') existing in the platform structure (1a), whereby the height of the recesses is arranged to correspond essentially at least to the thickness (h) of the frame part (x1).

2. Joint arrangement according to claim 1, characterized in, that the platform structure (1a) is arranged by single and square shaped platforms (1a"), that are placed preferably all over the bottom surface of the surface structure, whereby the framepart (x1) of the joint piece is arranged to embed preferably four platforms (1a").

3. Joint arrangement according to claim 1 or 2, characterized in, that at each corner of the surface structure there has been arranged two recesses (y2) one after the other at each side.

4. Joint arrangement according to any of the claims 1-3 in an essentially square shaped surface structure, whereby the joint arrangement comprises coupling means (z), such as male-female couplers (z1, z2) being placed at the outer edges of the surface structures, characterized in, that both the male and female couplers (z1, z2) are arranged at opposite outer edges of the surface structure.

5. Joint arrangement according to claim 4, characterized in, that the male couplers (z1) are arranged by projections being placed at the lower edges of the longitudinal (p1) outer edges of the surface structure and correspondingly the female couplers (z2) by recesses being placed at the lower edges of the crosswise (p2) outer edges.

6. Joint arrangement according to claim 4 or 5, characterized in, that the male and female couplers (z1, z2) comprise an auxiliary support/sealing assembly (z3), that is carried out by such as counterpart surfaces or the like being placed at the upper edge of the outer surface of the surface structure at an angle (α), that deviates essentially from the vertical direction, preferably at an angle of 15°, and being

directed to opposite directions and/or to the same direction in respect to the surface structure.

1/3









FIG. 1



3 / 3



1
INTERNATIONAL SEARCH REPORT

International application No.
PCT/FI 98/00307

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: E01C 13/04, E01C 5/20, E04F 15/10, A63C 19/12
According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: E01C, A63C, E04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 2558967 A1 (STEINKOPFF, DIETRICH), 7 July 1977 (07.07.77), figure 1 --	1-6
A	DE 2717625 A1 (ROYALTY S.A.), 27 October 1977 (27.10.77), figure 6, details 6a, 6b --	1-6
A	DE 3545748 A1 (BATTERMANN, WALTER), 25 June 1987 (25.06.87), detail 7 --	1-6
A	DE 4414341 A1 (PERMESANG, CLAUS), 14 Sept 1995 (14.09.95), abstract --	1-6

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance
 "E" earlier document but published on or after the international filing date
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
 "O" document referring to an oral disclosure, use, exhibition or other means
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

30 July 1998

Date of mailing of the international search report

05-08-1998

Name and mailing address of the ISA/
 Swedish Patent Office
 Box 5055, S-102 42 STOCKHOLM
 Facsimile No. +46 8 666 02 86

Authorized officer

Örjan Nylund
 Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 98/00307

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4568584 A (HOLLAND), 4 February 1986 (04.02.86), detail 46 --	1-6
A	EP 0077873 A1 (FIRMA CARL FREUDENBERG), 4 May 1983 (04.05.83), detail 2 -- -----	1-6

INTERNATIONAL SEARCH REPORT

Information on patent family members

30/06/98

International application No.

PCT/FI 98/00307

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 2558967 A1	07/07/77	NONE	
DE 2717625 A1	27/10/77	BE 853902 A CH 601568 A FR 2349680 A,B GB 1570451 A NL 7704559 A US 4161558 A	16/08/77 14/07/78 25/11/77 02/07/80 28/10/77 17/07/79
DE 3545748 A1	25/06/87	NONE	
DE 4414341 A1	14/09/95	DE 9403780 U EP 0671508 A	06/07/95 13/09/95
US 4568584 A	04/02/86	NONE	
EP 0077873 A1	04/05/83	SE 0077873 T3 DE 3142538 A	11/05/83